

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>6</sup> : <b>A61F 2/06</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 99/51166</b> (43) International Publication Date: 14 October 1999 (14.10.99)</p>
<p>(21) International Application Number: PCT/IE99/00020 (22) International Filing Date: 1 April 1999 (01.04.99) (30) Priority Data: 980241 2 April 1998 (02.04.98) IE (71) Applicant (for all designated States except US): SALVIAC LIMITED [IE/IE]; 39-40 Upper Mount Street, Dublin 2 (IE). (72) Inventor; and (75) Inventor/Applicant (for US only): GILSON, Paul [IE/IE]; Uggool, Moycullen, County Galway (IE). (74) Agents: O'CONNOR, Donal, H. et al.; Cruickshank &amp; Co., 1 Holles Street, Dublin 2 (IE).</p>		<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DE (Utility model), DK, DK (Utility model), EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b> With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p>
<p>(54) Title: DELIVERY CATHETER</p> <div data-bbox="451 1136 1128 1703" data-label="Image"> </div> <p>(57) Abstract</p> <p>A catheter (1) for transvascular deployment of a radially compressible medical device (16) has a tubular outer body (2) within which is slidably mounted an inner tubular sheath (3) which in turn houses a guide wire (4) which is axially movable through the sheath (3). The medical device (6) is mounted on the guide wire (4) and can be collapsed within the sheath (3) and body (2) for deployment. An outer distal end of the sheath (3) is provided with circumferentially spaced-apart axial slits (7) extending proximally from the distal end of the sheath (3) which sub-divide the distal end of the tubular side wall of the sheath (3) into a number of complementary tube sections (8) which are movable apart when the sheath (3) is pushed out of the distal end of the body (2) to engage or deploy the medical device (6).</p>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

- 1 -

"Delivery Catheter"Field of the Invention

The present invention relates to a catheter for delivery of implant devices of the general type comprising a loading means for enveloping the implant within a catheter tube and a releasable implant gripping means.

Background of the Invention

There are many forms of medical implant devices, deployed transvascularily by means of a catheter, which are used where there is a requirement to occlude a vessel, fill a void or plug a defect in the treatment of medical conditions, whether they be acute or chronic situations or cosmetic situations.

These medical implant devices are delivered either transarterially or transvenously. The medical implant device is loaded in a folded or collapsed position within a tip of a catheter. The tip of the catheter is directed to the defect which is to be repaired and then the medical implant device is delivered from the catheter. Once out of the catheter the medical implant device is expanded to its full size to occlude the defect. Many of the known medical implant devices used are unsuitable for some applications because of their size and rigidity and we have proposed in certain co-pending patent applications the provision of a replacement technology for conventionally used coils, wire frame occlusion devices and the like. These improved implant devices have included the provision of highly compressible implant devices such as those having a compressible porous polymeric structure. One of the problems, however, with compressible devices and indeed many other devices is that

- 2 -

they often do not react favourably to the conventional way of loading them in the catheter, which comprises pushing or pulling the implant into an end of the catheter. Very often by their very nature which allows them expand and assume the correct shape within the void this is the very construction that makes them difficult to push and manipulate. This also applies to other types of devices as well as implants having a compressible porous polymeric structure. Indeed what is required with most of these implants which can be loosely described as being expandable is that they be correctly compressed within the catheter. It is also desirable that if the implant device is initially deployed incorrectly or in the wrong location that the implant device can be easily loaded again in a collapsed position within the catheter for redeployment.

US 5,683,451 discloses apparatus and a method for endoluminal placement of intraluminal tubular prostheses such as grafts and stents. The devices are collapsed within a distal end of a delivery catheter by a set of spaced-apart hard elongate runners mounted at a distal end of an inner catheter slidable within the delivery catheter.

WO 98/14224 discloses apparatus and a method for retrieving partially deployed balloon expandable stents from within a vein or artery. The apparatus has a grasping device comprising either an expandable tube or a plurality of spaced-apart nitinol fingers with elastomeric web stretched therebetween. The tube or fingers can be manipulated to open to grasp a stent and then closed to grip the stent for withdrawal into a catheter.

US 5,026,377 discloses a device for the deployment or retraction of a self-expanding stent in a body canal. The device has a tubular outer sleeve and an inner core

- 3 -

slidable within the sleeve, the stent being collapsed against the core and being held in the collapsed state between the core and the outer sleeve for deployment.

- 5 It is an object of the present invention to provide a catheter that has the ability to deliver devices that don't have axial stiffness.

#### Summary of the Invention

10

According to the invention there is provided a catheter for transvascular deployment of a radially compressible medical device, comprising an elongate tubular outer body having a proximal end and a distal end, a tubular  
15 housing being formed at the distal end of the body for reception of the medical device in a collapsed state, a deployment means for engagement with the medical device being movable through the housing to move the medical device between a collapsed stored position within the  
20 housing and a deployment position externally of the housing, and loading means for radially collapsing the medical device for engagement within the housing, the loading means being movable relative to the body for engagement with the medical device,

25

characterised in that the loading means comprises a tubular sheath having a proximal end and a distal end, the distal end of the sheath being slidably mounted within the distal end of the body,

30

- 4 -

the distal end of the sheath having a tubular side wall with two or more slits in the side wall of the sheath extending proximally from a distal end of the sheath,

5

the slits sub-dividing the tubular side wall of the distal end of the sheath into a number of complementary tube sections which are movable between a closed position defining a tubular housing for  
10 reception of the medical device and an open position to enlarge the distal end of the sheath when the distal end of the sheath is moved outwardly of the distal end of the body.

15 By using a tubular loading means which is movable relative to the medical device for its securement, it is possible to grip the medical device in whatever way one requires and thus ensure that, for example, with a compressible or distortable medical device it is not compressed in an  
20 undesired way. Further, as the loading device is tubular, it provides continuous support fully around the medical device ensuring an even compression of the medical device. This is particularly desirable with foam type medical devices which do not have a support frame and so are  
25 easily distorted. The tubular loading means allows controlled compression of such medical devices so that they will open in a desired manner upon deployment.

In a preferred embodiment the slits in the distal end of  
30 the sheath comprise two or more circumferentially spaced-apart axially extending slits in the distal end of the

- 5 -

sheath.

In another embodiment the slits in the distal end of the sheath comprise two or more circumferentially spaced-apart  
5 helical slits in the distal end of the sheath.

In a further embodiment each tube section has an inner end hingedly connected to the sheath body by a hinge. Preferably each hinge is integrally formed with the  
10 sheath.

Conveniently each hinge may be biased to urge the tube section towards the open position.

15 In another embodiment a pair of slits are provided in the distal end of the sheath, sub-dividing the distal end of the sheath into two complementary tube sections hingedly connected at their inner ends to the sheath.

20 In a further embodiment three slits are provided in the distal end of the sheath, sub-dividing the distal end of the sheath into three complementary tube sections hingedly connected at their inner ends to the sheath.

25 In a further embodiment four slits are provided in the distal end of the sheath, sub-dividing the distal end of the sheath into four complementary tube sections hingedly connected at their inner ends to the sheath.

- 6 -

In another embodiment the deployment means for the medical device is a guidewire extending through the sheath.

Conveniently the catheter body is formed from a low  
5 friction material.

#### Brief Description of the Drawings

The invention will be more clearly understood from the  
10 following description of some embodiments thereof given by way of example only with reference to the accompanying drawings in which:-

15 Fig. 1 is a perspective view of a distal end of a catheter according to the invention;

Fig. 2 is a partially cut-away perspective view of the distal end of the catheter;

20 Fig. 3 is a view similar to Fig. 2 showing a compressible medical implant device loaded in the catheter for deployment;

25 Fig. 4 is a perspective view of the distal end of the catheter according to the invention;

Fig. 5 is an enlarged perspective view of a medical implant device for use with the catheter;

30 Fig. 6 is a sectional view showing the catheter in use in a first stage of deploying the implant device;

Fig. 7 is a view similar to Fig. 6 showing a second stage of the deployment of the implant device;



- 7 -

Fig. 8 is a view similar to Fig. 6 showing a third stage in the deployment of the implant device;

5 Fig. 9 is a perspective view similar to Fig. 4 showing another catheter according to a second embodiment of the invention;

10 Fig. 10 is an end elevational view of the catheter of Fig. 9;

Fig. 11 is a perspective view similar to Fig. 4 showing a further catheter according to a third embodiment of the invention;

15 Fig. 12 is an end elevational view of the catheter of Fig. 11; and

20 Fig. 13 is a detail perspective view of a split sheath forming portion of another catheter of the invention.

#### Description of the Preferred Embodiment

Referring to the drawings, and initially to Figs. 1 to 5  
25 thereof, there is illustrated a catheter according to the invention indicated generally by the reference numeral 1 and comprising an outer catheter tube 2 within which is slidably mounted an inner tubular sheath 3 which in turn houses a guide wire 4 which is slidable within the inner  
30 tubular sheath 3. At an outer end of the guide wire 4 is a gripper 5 of any suitable construction engaging a medical implant device 6 of compressible foam or other porous material. An outer end of the inner tubular sheath 3 is provided with four circumferentially spaced apart and  
35 axially arranged slits 7 which sub-divide the tubular side wall at the outer distal end of the inner tubular sheath 3

- 8 -

into four tube sections 8.

Each of the tube sections 8 is attached by a hinge joint 9 at an inner end of the tube section 8 to the inner support tube 3. Thus, each tube section 8 will pivot about the hinge joint 9 for movement between a closed position (Fig. 6) defining a tubular housing for reception of the medical implant device 6 and an open position (Figs. 4 and 8) to enlarge the distal end of the inner tubular sheath 3 when the distal end of the inner tubular sheath 3 is moved outwardly of the catheter 2 for reception or deployment of the medical implant device 6. It will be noted from Fig. 6 that when the medical device 6 is mounted within the inner tubular sheath 3 which is in a closed position retained within the distal end of the catheter 2, the medical implant device 6 is evenly compressed into a cylindrical configuration.

The implant device 6 illustrated in the drawings is shown in more detail in Fig. 5. The implant device 6 comprises a body 15 of a compressible porous plastics material of open-cell structure such as a plastic foam. Each end 16, 17 of the body 15 is flared outwardly in a trumpet shape. The foam body 15 is moulded about a platinum spring core 18 forming portion of the gripper 5 for attachment to the wire 4. It will be appreciated that this particular implant is chosen for illustration purposes only and the catheter of the invention is suitable for deploying many other types of compressible implant devices.

In use, to load the implant device 6 in the catheter 1 the gripper 5 at the end of the wire 4 is connected to the implant 6. The inner tubular sheath 3 is then pushed out of the outer catheter tube 2. As it is pushed out, the tube sections 8 will splay apart effectively creating a funnel. Upon withdrawal of the wire 4 the implant device

- 9 -

6 is withdrawn into the funnel thus created. Then the outer catheter tube 2 is advanced to capture the protruding end of the inner tubular sheath 3 which collapses the implant 6 radially in a controlled manner.

5 The implant device 6 is now housed within the outer catheter tube 2 in a collapsed position as shown in Fig. 6. The catheter 1 is then delivered transarterially or transvenously as required until an outer end of the catheter 1 is delivered to a desired location within a

10 vessel 10 as illustrated in Fig. 6. The outer catheter tube 2 is then withdrawn whilst holding the wire 4 and inner tubular sheath 3 steady. Next the inner tubular sheath 3 is partially withdrawn, as shown in Fig. 7, to establish a distal end of the implant device within the

15 vessel 10. As the inner tubular sheath 3 retracts the implant device 6 is free to expand to engage the vessel walls. If the physician is satisfied that the distal end of the implant device 6 is correctly positioned within the vessel 10, the inner tubular sheath 3 is retracted further

20 to release the proximal portion of the implant device which freely expands into the vessel 10 as shown in Fig. 8.

It will be appreciated that if by any chance the implant device 6 is not correctly positioned, that it can be

25 readily re-loaded in the catheter 1 and then correctly manipulated again into position in the opening and deployed as previously described. For example, the particular implant illustrated in the drawings would tend

30 to crumple if loaded, as is conventionally the case, when pushing in and out of the catheter tube. It will be appreciated that it is better to radially compress the implant than to pull or manipulate it axially. This is achieved by the inner tubular sheath 3 of the catheter 1

35 which radially compresses the implant device 6 as it is withdrawn into the outer catheter tube 2.

- 10 -

Referring now to Figs. 9 and 10, there is shown another catheter according to the invention indicated generally by the reference numeral 20. Parts similar to those described previously are assigned the same reference numerals. In this case, two slits 7 are provided at the distal end of the inner tubular sheath 3. Operation of the catheter 20 is similar to that described previously for the catheter of Figs. 1 to 8.

10

Referring now to Figs. 11 and 12, there is illustrated another catheter according to a third embodiment of the invention, indicated generally by the reference numeral 30. Parts similar to those described previously are assigned the same reference numerals. In this case, three slits 7 are provided at the distal end of the inner tubular sheath 3. Operation of the catheter 30 is similar to that described previously for the catheter of Figs. 1 to 8.

20

It will also be appreciated that any number of slits are possible at the outer end of the inner tubular sheath 3, however, ideally there should be at least two. Also different arrangements of the orientation and positioning of the slits at the distal end of the sheath are possible. Instead of extending axially as described above the slits may extend helically along the sheath. Helical arrangement is shown in Fig. 13 which shows a sheath 40 with helical slits 41.

30

It is envisaged that various forms of implant device may be used and that further the inner tubular sheath 3 and the outer catheter tube 2 may be manufactured from any suitable plastics material, or indeed any other flexible material.

35

- 11 -

The invention is not limited to the embodiments hereinbefore described which may be varied in both construction and detail within the scope of the appended claims.

- 12 -

CLAIMS

1. A catheter for transvascular deployment of a radially compressible medical device, comprising an elongate  
5 tubular outer body having a proximal end and a distal end, a tubular housing being formed at the distal end of the body for reception of the medical device in a collapsed state, a deployment means for engagement with the medical device being movable through the  
10 housing to move the medical device between a collapsed stored position within the housing and a deployment position externally of the housing, and loading means for radially collapsing the medical device for engagement within the housing, the loading  
15 means being movable relative to the body for engagement with the medical device,

characterised in that the loading means comprises a tubular sheath having a proximal end and a distal  
20 end, the distal end of the sheath being slidably mounted within the distal end of the body,

the distal end of the sheath having a tubular side wall with two or more slits in the side wall of the  
25 sheath extending proximally from a distal end of the sheath,

- 13 -

the slits sub-dividing the tubular side wall of the distal end of the sheath into a number of complementary tube sections which are movable between a closed position defining a tubular housing for reception of the medical device and an open position to enlarge the distal end of the sheath when the distal end of the sheath is moved outwardly of the distal end of the body.

2. A catheter as claimed in claim 1, wherein the slits in the distal end of the sheath comprise two or more circumferentially spaced-apart axially extending slits in the distal end of the sheath.

3. A catheter as claimed in claim 1, wherein the slits in the distal end of the sheath comprise two or more circumferentially spaced-apart helical slits in the distal end of the sheath.

4. A catheter as claimed in any preceding claim, wherein each tube section has an inner end hingedly connected to the sheath body by a hinge.

5. A catheter as claimed in claim 4, wherein each hinge is integrally formed with the sheath.

6. A catheter as claimed in claim 4 or claim 5 wherein

- 14 -

each hinge is biased to urge the tube section towards the open position.

- 5 7. A catheter as claimed in any preceding claim, wherein a pair of slits are provided in the distal end of the sheath, sub-dividing the distal end of the sheath into two complementary tube sections hingedly connected at their inner ends to the sheath.
- 10 8. A catheter as claimed in any of claims 1 to 6, wherein three slits are provided in the distal end of the sheath, sub-dividing the distal end of the sheath into three complementary tube sections hingedly connected at their inner ends to the sheath.
- 15 9. A catheter as claimed in any of claims claim 1 to 6, wherein four slits are provided in the distal end of the sheath, sub-dividing the distal end of the sheath into four complementary tube sections hingedly connected at their inner ends to the sheath.
- 20 10. A catheter as claimed in any preceding claim, wherein the deployment means for the medical device is a guidewire extending through the sheath.
- 25 11. A catheter as claimed in any preceding claim in which the catheter body is formed from a low friction



- 15 -

material.

5

1/6





Fig. 1


2/6

Fig. 2



3/6

Fig. 3



4/6

Fig. 4








Fig. 5



5/6

Fig. 6Fig. 7Fig. 8

6/6





Fig. 13

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/IE 99/00020

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 A61F2/06

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61F A61B A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98 06355 A (EDOGA) 19 February 1998 (1998-02-19) page 45, line 3 - page 46, line 4; figures 30-33	1, 2, 4-6, 9, 11
A	EP 0 696 447 A (CARDIOVASCULAR CONCEPTS, INC.) 14 February 1996 (1996-02-14) column 19, line 3 - line 50; figures 25-26B	1
A	WO 97 41778 A (SALVIAC LIMITED) 13 November 1997 (1997-11-13) figure 21	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

10 August 1999

Date of mailing of the international search report

17/08/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl

Authorized officer

Smith



# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IE 99/00020

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9806355 A	19-02-1998	AU 3904197 A	06-03-1998
EP 696447 A	14-02-1996	US 5683451 A	04-11-1997
		JP 8173548 A	09-07-1997
		US 5824041 A	20-10-1998
WO 9741778 A	13-11-1997	AU 3186897 A	26-11-1997
		EP 0900051 A	10-03-1999